

INDUCTIVE PROXIMITY SENSORS



IME18-08NNOZW2S | IME

INDUCTIVE PROXIMITY SENSORS



Ordering information

| Туре | Part no. |
|-----------------|----------|
| IME18-08NNOZW2S | 1040964 |

Included in delivery: BEF-MU-M18 (1)

Other models and accessories → www.sick.com/IME



Detailed technical data

| Features | |
|-----------------------------------|---|
| Housing | Metric |
| Housing | Standard design |
| Thread size | M18 x 1 |
| Diameter | Ø 18 mm |
| Sensing range S _n | 8 mm |
| Safe sensing range S _a | 6.48 mm |
| Installation type | Non-flush |
| Switching frequency | 1,000 Hz |
| Connection type | Cable, 3-wire, 2 m |
| Switching output | NPN |
| Output function | NC |
| Electrical wiring | DC 3-wire |
| Enclosure rating | IP67 ¹⁾ |
| Items supplied | Mounting nut, brass, nickel-plated (2x) |

¹⁾ According to EN 60529.

Mechanics/electronics

| Supply voltage | 10 V DC 30 V DC |
|--------------------------------|------------------|
| Ripple | ≤ 10 % |
| Voltage drop | $\leq 2 V^{(1)}$ |
| Time delay before availability | ≤ 100 ms |
| Hysteresis | 5 % 15 % |

 $^{1)}$ At I_a max.

 $^{2)}\ensuremath{\,\text{Supply voltage U}_B}$ and constant ambient temperature Ta.

³⁾ Of Sr.

IME18-08NNOZW2S | IME

INDUCTIVE PROXIMITY SENSORS

| Reproducibility | $\leq 2 \%^{(2)(3)}$ |
|--|-------------------------------|
| Temperature drift (of S _r) | ± 10 % |
| EMC | According to EN 60947-5-2 |
| Continuous current I _a | ≤ 200 mA |
| No load current | ≤ 10 mA |
| Cable material | PVC |
| Conductor size | 0.25 mm ² |
| Cable diameter | Ø 3.9 mm |
| Short-circuit protection | ✓ |
| Power-up pulse protection | ✓ |
| Shock and vibration resistance | 30 g, 11 ms/10 Hz 55 Hz, 1 mm |
| Ambient operating temperature | -25 °C +75 °C |
| Housing material | Brass, nickel-plated |
| Sensing face material | Plastic, PA 66 |
| Housing length | 67 mm |
| Thread length | 42 mm |
| Tightening torque, max. | ≤ 40 Nm |
| | |

¹⁾ At I_a max.

 $^{2)}\,\mbox{Supply voltage U}_{B}$ and constant ambient temperature Ta.

³⁾ Of Sr.

Safety-related parameters

| MTTF _D | 1,735 years |
|-------------------|-------------|
| DC _{avg} | 0 % |

Reduction factors

| Note | The values are reference values which may vary |
|----------------------------|--|
| St37 steel (Fe) | 1 |
| Stainless steel (V2A, 304) | Approx. 0.8 |
| Aluminum (AI) | Approx. 0.45 |
| Copper (Cu) | Approx. 0.4 |
| Brass (Br) | Approx. 0.4 |

Installation note

| Remark | Associated graphic see "Installation" |
|--------|---------------------------------------|
| A | 18 mm |
| В | 36 mm |
| c | 18 mm |
| D | 24 mm |
| E | 16 mm |
| F | 64 mm |

IME18-08NNOZW2S | IME


INDUCTIVE PROXIMITY SENSORS

Classifications

| ECLASS 5.0 | 27270101 |
|----------------|----------|
| ECLASS 5.1.4 | 27270101 |
| ECLASS 6.0 | 27270101 |
| ECLASS 6.2 | 27270101 |
| ECLASS 7.0 | 27270101 |
| ECLASS 8.0 | 27270101 |
| ECLASS 8.1 | 27270101 |
| ECLASS 9.0 | 27270101 |
| ECLASS 10.0 | 27270101 |
| ECLASS 11.0 | 27270101 |
| ECLASS 12.0 | 27274001 |
| ETIM 5.0 | EC002714 |
| ETIM 6.0 | EC002714 |
| ETIM 7.0 | EC002714 |
| ETIM 8.0 | EC002714 |
| UNSPSC 16.0901 | 39122230 |

Installation note

Non-flush installation




Connection diagram

Cd-003



Dimensional drawing (Dimensions in mm (inch))

IME18 Standard, cable, non-flush



① Connection

② Display LED

③ Fastening nuts (2x); width across 24, metal

Recommended accessories

Other models and accessories → www.sick.com/IME

| | Brief description | Туре | Part no. |
|---------------------------------|---|-------------|----------|
| Mounting bra | ckets and plates | | |
| | Mounting plate for M18 sensors, steel, zinc coated, without mounting hardware | BEF-WG-M18 | 5321870 |
| 40 | Mounting bracket for M18 sensors, steel, zinc coated, without mounting hardware | BEF-WN-M18 | 5308446 |
| Terminal and alignment brackets | | | |
| info Clar | Clamping block for round sensors M18, without fixed stop, plastic (PA12), glass-fiber re- inforced, mounting hardware included | BEF-KH-M18 | 2051481 |
| | Clamping block for round sensors M18, with fixed stop, plastic (PA12), glass-fiber rein- forced, mounting hardware included | BEF-KHF-M18 | 2051482 |

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

