

IME18-12BPSZWDK

IME

INDUCTIVE PROXIMITY SENSORS





Ordering information

Туре	Part no.
IME18-12BPSZWDK	1095534

Included in delivery: BEF-MU-M18 (1)

Other models and accessories → www.sick.com/IME



Detailed technical data

Features

HousingMetricHousingShort-bodyThread sizeM18 x 1DiameterØ 18 mmSensing range Sn12 mmSafe sensing range Sa9.72 mmInstallation typeQuasi-flushSwitching frequency500 HzConnection typeCable, 3-wire, 7 mSwitching outputPNPOutput functionNOElectrical wiringDC 3-wireEnclosure ratingIP67 1)Special featuresTriple sensing rangeItems suppliedMounting nut, brass, nickel-plated (2x)	reatures	
Thread size M18 x 1 Diameter Ø 18 mm Sensing range S _n 12 mm Safe sensing range S _a 9.72 mm Installation type Quasi-flush Switching frequency Connection type Cable, 3-wire, 7 m Switching output PNP Output function Electrical wiring Enclosure rating Special features M18 x 1 Ø 18 mm 12 mm Some Cable Quasi-flush Some Cable, 3-wire, 7 m Some Cable, 3-wire PNP DC 3-wire Enclosure rating IP67 1) Special features	Housing	Metric
Diameter Ø 18 mm Sensing range S _n 12 mm Safe sensing range S _a 9.72 mm Installation type Quasi-flush Switching frequency 500 Hz Connection type Cable, 3-wire, 7 m Switching output PNP Output function NO Electrical wiring DC 3-wire Enclosure rating IP67 ¹⁾ Special features Triple sensing range	Housing	Short-body
Sensing range S _n 12 mm Safe sensing range S _a 9.72 mm Installation type Quasi-flush Switching frequency 500 Hz Connection type Cable, 3-wire, 7 m Switching output PNP Output function Electrical wiring Enclosure rating IP67 1) Special features 12 mm 9.72 mm Quasi-flush Source Cable, 3-wire, 7 m PNP PNP Output function IP67 1) Special features	Thread size	M18 x 1
Safe sensing range S _a Installation type Quasi-flush Switching frequency Connection type Cable, 3-wire, 7 m Switching output PNP Output function NO Electrical wiring Enclosure rating IP67 1) Special features 9.72 mm Quasi-flush Southout Function NO PNP NO Triple sensing range	Diameter	Ø 18 mm
Installation type Switching frequency Connection type Cable, 3-wire, 7 m PNP Output function Electrical wiring Enclosure rating IP67 1) Triple sensing range	Sensing range S _n	12 mm
Switching frequency Connection type Cable, 3-wire, 7 m Switching output PNP Output function NO Electrical wiring DC 3-wire Enclosure rating IP67 1) Special features Triple sensing range	Safe sensing range S _a	9.72 mm
Connection type Switching output PNP Output function Electrical wiring Enclosure rating IP67 1) Triple sensing range	Installation type	Quasi-flush
Switching output Output function NO Electrical wiring DC 3-wire Enclosure rating IP67 1) Special features Triple sensing range	Switching frequency	500 Hz
Output function Electrical wiring DC 3-wire Enclosure rating IP67 1) Special features Triple sensing range	Connection type	Cable, 3-wire, 7 m
Electrical wiring DC 3-wire Enclosure rating IP67 1) Special features Triple sensing range	Switching output	PNP
Enclosure rating IP67 1) Special features Triple sensing range	Output function	NO
Special features Triple sensing range	Electrical wiring	DC 3-wire
	Enclosure rating	IP67 ¹⁾
Items supplied Mounting nut, brass, nickel-plated (2x)	Special features	Triple sensing range
	Items supplied	Mounting nut, brass, nickel-plated (2x)

¹⁾ According to EN 60529.

Mechanics/electronics

Supply voltage	10 V DC 30 V DC
Ripple	≤ 10 %
Voltage drop	\leq 2 V $^{1)}$
Time delay before availability	≤ 50 ms

¹⁾ At I may

 $^{^{\}rm 2)}$ Supply voltage U_{B} and constant ambient temperature Ta.

³⁾ Of Sr.

Hysteresis	1 % 15 %
Reproducibility	\leq 5 % $^{2) (3)}$
Temperature drift (of S _r)	± 10 %
EMC	According to EN 60947-5-2
Continuous current I _a	≤ 200 mA
No load current	≤ 10 mA
Cable material	PVC
Conductor size	0.25 mm ²
Cable diameter	Ø 3.9 mm
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	30 g, 11 ms/10 Hz 55 Hz, 1 mm
Ambient operating temperature	-25 °C +75 °C
Ambient temperature, storage	-25 °C +75 °C
Housing material	Brass, nickel-plated
Sensing face material	Plastic, PA 66
Housing length	48 mm
Thread length	33 mm
Tightening torque, max.	≤ 30 Nm
UL File No.	NRKH.E181493

 $^{^{1)}}$ At I $_{\rm a}$ max.

Safety-related parameters

MTTF _D	1,735 years
DC _{avg}	0 %

Reduction factors

Note	The values are reference values which may vary	
St37 steel (Fe)	1	
Stainless steel (V2A, 304)	Approx. 0.78	
Aluminum (AI)	Approx. 0.43	
Copper (Cu)	Approx. 0.35	
Brass (Br)	Approx. 0.47	

Installation note

Remark	Associated graphic see "Installation"
A	13.5 mm
В	35 mm
C	18 mm
D	36 mm
E	4 mm


 $^{^{\}rm 2)}$ Supply voltage $\rm U_B$ and constant ambient temperature Ta.


³⁾ Of Sr.

F	120 mm
Classifications	
ECLASS 5.0	27270101
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101
ECLASS 6.2	27270101
ECLASS 7.0	27270101
ECLASS 8.0	27270101
ECLASS 8.1	27270101
ECLASS 9.0	27270101
ECLASS 10.0	27270101
ECLASS 11.0	27270101
ECLASS 12.0	27274001
ETIM 5.0	EC002714
ETIM 6.0	EC002714
ETIM 7.0	EC002714
ETIM 8.0	EC002714
UNSPSC 16.0901	39122230

Installation note

Quasi-flush installation






Connection diagram

Cd-001



Dimensional drawing (Dimensions in mm (inch))

IME18 Short-body housing, cable, flush



- ① Connection
- ② Display LED
- ③ Fastening nuts (2x); width across 24, metal

Recommended accessories

Other models and accessories → www.sick.com/IME

	Brief description	Туре	Part no.
Mounting brackets and plates			
	Mounting plate for M18 sensors, steel, zinc coated, without mounting hardware	BEF-WG-M18	5321870
40	Mounting bracket for M18 sensors, steel, zinc coated, without mounting hardware	BEF-WN-M18	5308446
Terminal and alignment brackets			
	Clamping block for round sensors M18, without fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included $$	BEF-KH-M18	2051481
	Clamping block for round sensors M18, with fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included $$	BEF-KHF-M18	2051482

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

