# IMG18-12BPSZW5KS02

**INDUCTIVE PROXIMITY SENSORS** 



INDUCTIVE PROXIMITY SENSORS



#### Ordering information

Туре	Part no.
IMG18-12BPSZW5KS02	1102289

Included in delivery: BEF-MU-M18 (1)

Other models and accessories → www.sick.com/IME

Illustration may differ



#### Detailed technical data

#### Features

Housing	Metric
Housing	Extremely short model
Thread size	M18 x 1
Diameter	Ø 18 mm
Sensing range S <sub>n</sub>	12 mm
Safe sensing range S <sub>a</sub>	9.72 mm
Installation type	Quasi-flush
Switching frequency	500 Hz
Connection type	Cable, 3-wire, 5 m
Switching output	PNP
Output function	NO
Electrical wiring	DC 3-wire
Enclosure rating	IP67 <sup>1)</sup>
Special features	Triple sensing range
Items supplied	Mounting nut, brass, nickel-plated (2x)

<sup>1)</sup> According to EN 60529.

#### Mechanics/electronics

Supply voltage	10 V DC 30 V DC
Ripple	≤ 10 %
Voltage drop	$\leq 2 V^{(1)}$

 $^{1)}$  At I<sub>a</sub> max.

 $^{2)}$  Supply voltage  $U_{B}$  and constant ambient temperature Ta.

<sup>3)</sup> Of Sr.

INDUCTIVE PROXIMITY SENSORS

Hysteresis	3 % 20 %
Reproducibility	$\leq 2 \%^{(2)(3)}$
Temperature drift (of S <sub>r</sub> )	± 10 %
EMC	According to EN 60947-5-2
Continuous current I <sub>a</sub>	≤ 200 mA
No load current	≤ 10 mA
Cable material	PVC
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	100 g / 2 ms / 500 cycles; 150 g / 1 Mio cycles; 10 Hz 55 Hz / 1 mm; 55 Hz 500 Hz / 60 g
Ambient operating temperature	-25 °C +75 °C
Housing material	Brass, nickel-plated
Sensing face material	Plastic, LCP
Housing length	31 mm
Thread length	26 mm
Tightening torque, max.	Typ. 12 Nm
UL File No.	E181493

<sup>1)</sup> At I<sub>a</sub> max.

 $^{\rm 2)}$  Supply voltage  $U_{\rm B}$  and constant ambient temperature Ta.

<sup>3)</sup> Of Sr.

### Safety-related parameters

MTTFD	1,971 years
DC <sub>avg</sub>	0 %
T <sub>M</sub> (mission time)	20 years

#### **Reduction factors**

Note	The values are reference values which may vary	
St37 steel (Fe)	1	
Stainless steel (V2A, 304)	Approx. 0.5	
Aluminum (AI)	Approx. 0.3	
Copper (Cu)	Approx. 0.23	
Brass (Br)	Approx. 0.32	

#### Installation note

Remark	Associated graphic see "Installation"
A	13.5 mm
В	35 mm
c	18 mm
D	36 mm
E	4 mm
F	120 mm

INDUCTIVE PROXIMITY SENSORS

#### Classifications

ECLASS 5.0	27270101
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101
ECLASS 6.2	27270101
ECLASS 7.0	27270101
ECLASS 8.0	27270101
ECLASS 8.1	27270101
ECLASS 9.0	27270101
ECLASS 10.0	27270101
ECLASS 11.0	27270101
ECLASS 12.0	27274001
ETIM 5.0	EC002714
ETIM 6.0	EC002714
ETIM 7.0	EC002714
ETIM 8.0	EC002714
UNSPSC 16.0901	39122230


#### **Connection diagram**

Cd-001



#### Dimensional drawing (Dimensions in mm (inch))

Extremely short IMG18 model, cable, flush



INDUCTIVE PROXIMITY SENSORS

#### **Recommended accessories**

Other models and accessories -> www.sick.com/IME

	Brief description	Туре	Part no.	
Mounting bra	Mounting brackets and plates			
	Mounting plate for M18 sensors, steel, zinc coated, without mounting hardware	BEF-WG-M18	5321870	
40	Mounting bracket for M18 sensors, steel, zinc coated, without mounting hardware	BEF-WN-M18	5308446	
Terminal and alignment brackets				
	Clamping block for round sensors M18, without fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included $% \left( \frac{1}{2}\right) =0$	BEF-KH-M18	2051481	
	Clamping block for round sensors M18, with fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included	BEF-KHF-M18	2051482	

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

