

# LL3-DK08

Fiber-optic cables

**FIBERS** 





## Ordering information

Туре	Part no.
LL3-DK08	5350097

Other models and accessories → www.sick.com/Fiber-optic\_cables

#### Detailed technical data

#### **Features**

Davies type	Fiber-optic cables
Device type	riber-optic cables
Functional principle	Proximity system
Fiber-optic head design	Threaded sleeve
Application	Standard
Compatible fiber-optic amplifiers	WLL80, WLL180, GLL170(T)
Sensing range max.	Depending on the fiber optic amplifier used
Minimal object diameter	0.015 mm <sup>1)</sup>
Optical fiber head	
Angle of dispersion	60°
Integrated lens	No
Compatibility tip adapters	Yes
Optical fiber	
Compatibility with infrared light	No
Optical fiber cable can be shortened	✓
Adapter end sleeves required	Yes
Included with delivery	Mounting, 2 x M3 hexagon nut, 1 x washer, FC fiber cutter (LLAC-FC 2119448), adapter sleeves LLAC-AB13 (1.3 mm)

 $<sup>^{1)}</sup>$  Minimum detectable object was determined at optimum measuring distance and optimum setting.

#### Mechanics

Optical fiber head	
Light emission	Axial
Thread diameter (housing)	M3
Optical fiber taper diameter	≥ 2 mm
Optical fiber taper length after 2 mm	≥ 1 mm
Optical fiber	
Fiber length	2,000 mm
Bending radius	1 mm
Dynamic flexibility (robotics)	No
Outside diameter, optical fiber cable connection	1.3 mm
Fiber arrangement	Singlefiber

 $<sup>^{1)}</sup>$  C = Coaxial, S = Sender, E = Receiver.

<sup>&</sup>lt;sup>2)</sup> Stainless steel SUS303.

Core structure	2 x Ø 0,5 mm <sup>1)</sup> Singlefiber
Material	
Optical fiber head	Stainless steel <sup>2)</sup>
Sheath	Polyethylen (PE)
Fibers	Polymethylmethacrylat (PMMA)
Weight	18 g

 $<sup>^{1)}</sup>$  C = Coaxial, S = Sender, E = Receiver.

#### Ambient data


Ambient operating temperature	-55 °C +70 °C
-------------------------------	---------------

#### Classifications

ECLASS 5.0	27270905
ECLASS 5.1.4	27270905
ECLASS 6.0	27270905
ECLASS 6.2	27270905
ECLASS 7.0	27270905
ECLASS 8.0	27270905
ECLASS 8.1	27270905
ECLASS 9.0	27270905
ECLASS 10.0	27270905
ECLASS 11.0	27270905
ECLASS 12.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
ETIM 8.0	EC002651
UNSPSC 16.0901	39121528

## Dimensional drawing (Dimensions in mm (inch))

#### LL3-DK08



<sup>2)</sup> Stainless steel SUS303.

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

