



# MPS-025CLTU0

MPS-C

POSITION SENSORS

**SICK**  
Sensor Intelligence.



### Ordering information

| Type         | Part no. |
|--------------|----------|
| MPS-025CLTU0 | 1079359  |

Other models and accessories → [www.sick.com/MPS-C](http://www.sick.com/MPS-C)



### Detailed technical data

#### Features

|                                    |  |
|------------------------------------|--|
| <b>Cylinder type</b>               | C-slot   |
| <b>Cylinder types with adapter</b> | Round body cylinder<br>Profile cylinders and tie-rod cylinders<br>SMC rail CDQ2<br>SMC rail ECDQ2  |
| <b>Measuring range</b>             | 25 mm <sup>1)</sup>  |
| <b>Housing length</b>              | 41 mm  |
| <b>Switching output</b>            | Push-pull: PNP/NPN   |
| <b>Output function</b>             | Analog, IO-Link, Switching output  |
| <b>Electrical wiring</b>           | DC 4-wire  |
| <b>Analog output (voltage)</b>     | 0 V ... 10 V   |
| <b>Analog output (current)</b>     | 4 mA ... 20 mA   |
| <b>Enclosure rating</b>            | IP67 <sup>2)</sup>   |
| <b>Adjustment</b>                  |  |
| Teach-in control panel             | Teaching in analog outputs<br>Selecting the current/voltage output<br>Inverting the analog output<br>Teaching in digital switching outputs   |
| IO-Link                            | Teaching in 4 switching points<br>Pin 2 configuration (0 V–10 V, 4 mA–20 mA)<br>Measuring range (mm) teach-in (analog output)<br>Disabling teach-in pushbutton<br>Teach-in modes per output via IO-Link (cylinder switch mode, two point mode, window mode, and single point mode) |

<sup>1)</sup> ± 1 mm.

<sup>2)</sup> According to EN 60529.

Mechanics/electronics

|  |  |
|--|--|
| <b>Supply voltage</b>                            | 12 V DC ... 30 V DC  |
| <b>Power consumption</b>                         | 42 mA, without load  |
| <b>Voltage drop</b>                              | ≤ 2 V  |
| <b>Continuous current I<sub>a</sub></b>          | ≤ 100 mA <sup>1)</sup>   |
| <b>Max. load resistance</b>                      | ≤ 500 Ω Power Output, at 24 V  |
| <b>Min. load resistance</b>                      | ≥ 2 kΩ <sup>2)</sup>   |
| <b>Protection class</b>                          | III  |
| <b>Time delay before availability</b>            | 0.15 s   |
| <b>Required magnetic field sensitivity, typ.</b> | 3 mT ... 12 mT   |
| <b>Resolution, typ.</b>                          | ≥ 50 μm  |
| <b>Linearity error, typ.</b>                     | 0.3 mm <sup>3)</sup>   |
| <b>Repeat accuracy, typ.</b>                     | 0.1 mm <sup>4)</sup>   |
| <b>Sampling rate, typ.</b>                       | 1 ms   |
| <b>Reverse polarity protection</b>               | Yes  |
| <b>Short-circuit protection</b>                  | Yes  |
| <b>Status indicator LED</b>                      | Yes  |
| <b>Digital switching output</b>                  | Yes  |
| <b>Teach-in</b>                                  | Yes  |
| <b>Ambient operating temperature</b>             | -20 °C ... +70 °C  |
| <b>Shock and vibration resistance</b>            | 30 g, 11 ms / 10 ... 55 Hz, 1 mm   |
| <b>EMC</b>                                       | According to EN 60947-5-7 <sup>5)</sup>  |
| <b>Connection type</b>                           | Cable, 4-wire, 2 m   |
| <b>Connection type Detail</b>                    |  |
| Deep-freeze property                             | Do not bend below 0 °C   |
| Conductor cross section                          | 0.08 mm <sup>2</sup>   |
| Cable diameter                                   | Ø 2.6 mm   |
| Bending radius                                   | With fixed installation > 5 x cable diameter<br>For flexible use > 10 x cable diameter |
| Cable outlet                                     | Axial  |
| <b>Material</b>                                  |  |
| Housing  | Plastic  |
| Cable  | PUR  |
| <b>UL File No.</b>                               | NRKH.E181493 & NRKH7.E181493   |

<sup>1)</sup> ≤ 100 mA (PUSH); ≥ -100 mA (PULL).

<sup>2)</sup> Voltage output.

<sup>3)</sup> At 25 °C, linearity error (maximum deviation) depending on response curve and minimal deviation function.

<sup>4)</sup> At 25 °C, repeatability magnet movement in one direction.

<sup>5)</sup> The analog measured value can deviate under transient conditions.

Safety-related parameters

|                         |           |
|-------------------------|-----------|
| <b>MTTF<sub>D</sub></b> | 244 years |
| <b>DC<sub>avg</sub></b> | 0 %       |

|                                     |          |
|-------------------------------------|----------|
| <b>T<sub>M</sub> (mission time)</b> | 20 years |
|-------------------------------------|----------|


### Communication interface

|                                       |  |
|---------------------------------------|--|
| <b>Communication interface</b>        | IO-Link V1.1   |
| <b>Communication Interface detail</b> | COM3   |
| <b>Cycle time</b>                     | 1 ms   |
| <b>Process data length</b>            | 16 Bit   |
| <b>Process data structure</b>         | Bit 0 = switching signal Q <sub>L1</sub><br>Bit 1 = switching signal Q <sub>L2</sub><br>Bit 2 = switching signal Q <sub>L3</sub><br>Bit 3 = switching signal Q <sub>L4</sub><br>Bit 4 ... 15 = position (in 50 µm) |

### Classifications


|                       |          |
|-----------------------|----------|
| <b>ECLASS 5.0</b>     | 27270104 |
| <b>ECLASS 5.1.4</b>   | 27270104 |
| <b>ECLASS 6.0</b>     | 27270104 |
| <b>ECLASS 6.2</b>     | 27270104 |
| <b>ECLASS 7.0</b>     | 27270104 |
| <b>ECLASS 8.0</b>     | 27270104 |
| <b>ECLASS 8.1</b>     | 27270104 |
| <b>ECLASS 9.0</b>     | 27270104 |
| <b>ECLASS 10.0</b>    | 27270104 |
| <b>ECLASS 11.0</b>    | 27270104 |
| <b>ECLASS 12.0</b>    | 27274301 |
| <b>ETIM 5.0</b>       | EC002544 |
| <b>ETIM 6.0</b>       | EC002544 |
| <b>ETIM 7.0</b>       | EC002544 |
| <b>ETIM 8.0</b>       | EC002544 |
| <b>UNSPSC 16.0901</b> | 39122230 |

### Installation note




## Connection diagram

Cd-358



## Dimensional drawing (Dimensions in mm (inch))

Cable





- ① Teach-in button
- ② Status LEDs
- ③ Operating LEDs
- ④ Fixing screw SW 1.5
- ⑤ Connection

## Recommended accessories

Other models and accessories → [www.sick.com/MPS-C](http://www.sick.com/MPS-C)

|                                      | Brief description  | Type                              | Part no. |
|--------------------------------------|--|-----------------------------------|----------|
| <b>Connection modules</b>            |  |                                   |          |
|                                      | IO-Link V1.1 Class A port, USB2.0 port, optional external power supply 24V / 1A  | IOLA2US-01101 (SiLink2 Master)    | 1061790  |
|                                      | PROFINET IO-Link Master, IO-Link V1.1, Port Class A, power supply via 7/8" cable 24 V / 8 A, fieldbus connection via M12 cable | IOLG2PN-03208R01 (IO-Link Master) | 6053253  |
| <b>Brackets for cylinder sensors</b> |  |                                   |          |
|                                      | Mounting bracket for integrated profile cylinder/tie-rod cylinder, zinc diecast, mounting hardware included                    | BEF-KHZ-PC1                       | 2076170  |

|   | Brief description   | Type            | Part no. |
|---|---|-----------------|----------|
|  | 1 piece, Mounting bracket on round body cylinder with piston diameter of 1 mm ... 130 mm, ambient temperature min -30 °C max 80 °C, stainless steel, Aluminum | BEF-KHZ-RC1-130 | 2077686  |
|   | 1 piece, Mounting bracket on round body cylinder with piston diameter of 1 mm ... 25 mm, ambient temperature min -30 °C max 80 °C, stainless steel, Aluminum  | BEF-KHZ-RC1-25  | 2077685  |
| Other mounting accessories  |   |                 |          |
|  | 10 pieces, Label Holder, 2.5 mm to 3.5 mm, 10 pcs., TPU   | LABEL HOLDER    | 2086019  |

### Recommended services

Additional services → [www.sick.com/MPS-C](https://www.sick.com/MPS-C)

|  | Type                   | Part no.   |
|--|------------------------|------------|
| Function Block Factory   |                        |            |
| <ul style="list-style-type: none"> <li>• <b>Description:</b> The Function Block Factory supports common programmable logic controllers (PLCs) from various manufacturers, such as Siemens, Beckhoff, Rockwell Automation and B&amp;R. More information on the FBF can be found <a _blank"&gt;="" a="" here<="" href="https://fbf.cloud.sick.com target=">.</a></li> <li>• <b>Note:</b> You can configure your function block at <a _blank"&gt;="" a="" block="" factory<="" function="" href="https://fbf.cloud.sick.com target=">. As a login please use your SICK ID.</a></li> </ul> | Function Block Factory | On request |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)