

YF2A2B-050VH2M2A2B

Sensor/actuator cable

SICK
Sensor Intelligence.



Ordering information

Type	Part no.
YF2A2B-050VH2M2A2B	2130957

Other models and accessories → www.sick.com/Sensor_actuator_cable

Detailed technical data

Technical specifications




Connection type head A	Female connector, M12, 12-pin, straight, A-coded						
Connection type head B	Male connector, M12, 12-pin, straight						
Locking plug connector	Screw connection						
Connector material	TPU						
Connector color	Black						
Locking nut material	Zinc die-cast, nickel-plated						
Seal material	FKM						
Tightening torque	0.6 Nm						
Width across flats	13						
Cable	5 m, 12-wire, PVC						
Jacket material	PVC						
Jacket color	Gray						
Cable diameter	6.5 mm						
Conductor cross section	0.14 mm ²						
Shielding	Shielded						
Bending radius	<table border="0"> <tr> <td>Flexible use</td> <td>> 15 x cable diameter</td> </tr> <tr> <td>Stationary position</td> <td>> 10 x cable diameter</td> </tr> <tr> <td>Drag chain operation</td> <td>-</td> </tr> </table>	Flexible use	> 15 x cable diameter	Stationary position	> 10 x cable diameter	Drag chain operation	-
Flexible use	> 15 x cable diameter						
Stationary position	> 10 x cable diameter						
Drag chain operation	-						
Rated impulse voltage	0.8 kV						
Current loading	≤ 1.5 A						
Signal type	Sensor/actuator cable						
Application	Zones with chemicals Uncontaminated zones						
Authorizations	UL CE						
UL File No.	E335179						
Enclosure rating	IP65 / IP66K / IP67						
Operating temperature	<table border="0"> <tr> <td>Flexible use</td> <td>-5 °C ... +80 °C</td> </tr> <tr> <td>Stationary position</td> <td>-30 °C ... +80 °C</td> </tr> <tr> <td>Head</td> <td>-25 °C ... +85 °C</td> </tr> </table>	Flexible use	-5 °C ... +80 °C	Stationary position	-30 °C ... +80 °C	Head	-25 °C ... +85 °C
Flexible use	-5 °C ... +80 °C						
Stationary position	-30 °C ... +80 °C						
Head	-25 °C ... +85 °C						
Contamination rating	3						

Insulation resistance	100 MΩ
Overvoltage category	III
Specific insulation resistance	30 mΩ

Classifications

ECLASS 5.0	19030312
ECLASS 5.1.4	19030312
ECLASS 6.0	27060304
ECLASS 6.2	27060304
ECLASS 7.0	27060304
ECLASS 8.0	27060304
ECLASS 8.1	27060304
ECLASS 9.0	27060304
ECLASS 10.0	27060304
ECLASS 11.0	27060304
ECLASS 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

Dimensional drawing (Dimensions in mm (inch))



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com