



# YG2A68-400XXXLECX

Sensor/actuator cable

**SICK**  
Sensor Intelligence.



Illustration may differ

## Ordering information

Type	Part no.
YG2A68-400XXXLECX	2121385

Other models and accessories → [www.sick.com/Sensor\\_actuator\\_cable](http://www.sick.com/Sensor_actuator_cable)

## Detailed technical data

### Technical specifications


<b>Connection type head A</b>	Female connector, M12, 8-pin, angled, A-coded								
<b>Connection type head B</b>	Flying leads								
<b>Locking plug connector</b>	Screw connection								
<b>Connector material</b>	CuZn								
<b>Locking nut material</b>	Nickel-plated brass								
<b>Seal material</b>	FKM								
<b>Cable</b>	40 m, 8-wire, 8 wires, 4 x 2 twisted in pairs, PUR, halogen-free								
<b>Jacket material</b>	PUR, halogen-free								
<b>Cable diameter</b>	7 mm								
<b>Conductor cross section</b>	0.25 mm <sup>2</sup>								
<b>Shielding</b>	Shielded								
<b>Bending radius</b>	<table border="0"> <tr> <td style="padding-right: 20px;">Flexible use</td> <td>&gt; 10 x cable diameter</td> </tr> <tr> <td>Stationary position</td> <td>&gt; 5 x cable diameter</td> </tr> </table>	Flexible use	> 10 x cable diameter	Stationary position	> 5 x cable diameter				
Flexible use	> 10 x cable diameter								
Stationary position	> 5 x cable diameter								
<b>Bending cycles</b>	> 2,000,000								
<b>Traversing speed</b>	≤ 3.3 m/s								
<b>Acceleration</b>	≤ 5 m/s <sup>2</sup>								
<b>Signal type</b>	RS-422, SSI								
<b>Enclosure rating</b>	IP67								
<b>Specialty</b>	Very good oil and chemical resistance								
<b>Operating temperature</b>	<table border="0"> <tr> <td style="padding-right: 20px;">Flexible use</td> <td>-25 °C ... +80 °C</td> </tr> <tr> <td>Stationary position</td> <td>-50 °C ... +80 °C</td> </tr> <tr> <td>Drag chain operation</td> <td>-25 °C ... +60 °C</td> </tr> <tr> <td>Head</td> <td>-25 °C ... +85 °C</td> </tr> </table>	Flexible use	-25 °C ... +80 °C	Stationary position	-50 °C ... +80 °C	Drag chain operation	-25 °C ... +60 °C	Head	-25 °C ... +85 °C
Flexible use	-25 °C ... +80 °C								
Stationary position	-50 °C ... +80 °C								
Drag chain operation	-25 °C ... +60 °C								
Head	-25 °C ... +85 °C								

### Classifications

<b>ECLASS 5.0</b>	19030312
<b>ECLASS 5.1.4</b>	19030312
<b>ECLASS 6.0</b>	27060304
<b>ECLASS 6.2</b>	27060304

<b>ECLASS 7.0</b>	27060304
<b>ECLASS 8.0</b>	27060304
<b>ECLASS 8.1</b>	27060304
<b>ECLASS 9.0</b>	27060304
<b>ECLASS 10.0</b>	27060304
<b>ECLASS 11.0</b>	27060304
<b>ETIM 5.0</b>	EC000830
<b>ETIM 6.0</b>	EC000830
<b>ETIM 7.0</b>	EC003249
<b>ETIM 8.0</b>	EC003249
<b>UNSPSC 16.0901</b>	26121604

PIN assignment



- ① White
- ② Brown
- ③ Green
- ④ Yellow
- ⑤ Gray
- ⑥ Pink
- ⑦ Blue
- ⑧ Red

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)