



# YM12ES4-0075S5586D

Field-wireable connectors

**SICK**  
Sensor Intelligence.



## Ordering information

| Type               | Part no. |
|--------------------|----------|
| YM12ES4-0075S5586D | 2109773  |

Please consider the operational voltage of the connector. For sensors with an integrated cable and flying leads the operational voltage of the connector can be lower than the operational voltage of the sensor.

Other models and accessories → [www.sick.com/Field-wireable\\_connectors](http://www.sick.com/Field-wireable_connectors)

## Detailed technical data

### Technical specifications


|                                |   |
|--------------------------------|---|
| <b>Connection type head A</b>  | Male connector, M12, 4-pin, straight, D-coded |
| <b>Connection type</b>         | Screw-type terminals                          |
| <b>Connector material</b>      | Stainless steel (V4A/1.4404/316L)             |
| <b>Connector color</b>         | Silver  |
| <b>Locking nut material</b>    | Stainless steel (V4A/1.4404)                  |
| <b>Conductor cross section</b> | 0.5 mm <sup>2</sup>                           |
| <b>Shielding</b>               | Shielded                                      |
| <b>Permitted cross-section</b> | ≤ 0.75 mm <sup>2</sup>                        |
| <b>Reference voltage</b>       | ≤ 30 V  |
| <b>Rated impulse voltage</b>   | 48 V AC                                       |
| <b>Current loading</b>         | ≤ 4 A   |
| <b>Application</b>             | Hygienic and washdown zones                   |
| <b>Enclosure rating</b>        | IP69K   |
| <b>Operating temperature</b>   | Head -40 °C ... +85 °C                        |
| <b>Contamination rating</b>    | 3   |
| <b>Overvoltage category</b>    | II  |

### Classifications

|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27279290 |
| <b>ECLASS 5.1.4</b> | 27279290 |
| <b>ECLASS 6.0</b>   | 27279221 |
| <b>ECLASS 6.2</b>   | 27279221 |
| <b>ECLASS 7.0</b>   | 27440104 |
| <b>ECLASS 8.0</b>   | 27440104 |
| <b>ECLASS 8.1</b>   | 27440104 |
| <b>ECLASS 9.0</b>   | 27440102 |
| <b>ECLASS 10.0</b>  | 27440102 |
| <b>ECLASS 11.0</b>  | 27440102 |

|                       |          |
|-----------------------|----------|
| <b>ECLASS 12.0</b>    | 27440116 |
| <b>ETIM 5.0</b>       | EC002635 |
| <b>ETIM 6.0</b>       | EC002635 |
| <b>ETIM 7.0</b>       | EC002635 |
| <b>ETIM 8.0</b>       | EC002635 |
| <b>UNSPSC 16.0901</b> | 39121421 |

Dimensional drawing (Dimensions in mm (inch))



## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)